










AL789_V

Fibre Glass Stopper

Description	AUTOLUX® Fibre Glass Stopper, AL789 , is a polyester based stopper which contains special glass fibres. It has very good adhesion, mechanical strength, filling and sanding properties.		
Products	Stopper: Hardener:	AL789 <i>Autolux</i> Fibre Glass Stopper SHA305 <i>Autolux</i> Hardener for AL789	
Substrates	Bare metal: steel, galvanized steel and aluminium SMC and FRP Old finishes in sound condition		
Surface Preparation		Bare metal: Scuff well Old finishes: Machine sand P80-P180 grit	 Degrease the surface thoroughly before and after sanding. Before application the surface must be completely dry.
Mixing		<i>Autolux</i> Fibre Glass Stopper AL789 <i>Autolux</i> Hardener SHA305	By weight: 100 Parts 2 - 3 Parts
	Working Time: 4 - 5 min, depending on temperature and proportion of hardener		
Application		Use a suitable knife or spreader.	
Drying		Stopper dry to sand on 20 – 30 min. at 20°C. I.R - Short Wave 2 – 3 minutes* - Medium Wave 5 – 7 minutes* *Depending on IR equipment used	
Sanding		Dry: P80–P120, to desired contour. P120 – P240 to finish	
Recoat		Note: <i>Autolux</i> Fibre Glass Stopper AL789, must be overcoated with <i>Autolux</i> Universal Stopper (AL785) or <i>Autolux</i> Soft Stopper (AL787) prior to recoating. Stopper can be recoated with <i>Autolux</i> CFE Primer, Epoxy Primer or 2K Primer Surfacer.	
Process Notes	Clean up equipment immediately after use, using <i>Autolux</i> Thinner or another suitable solvent. Dispose of waste in accordance with applicable regulations.		
VOC Information	The EU limit value for this product (product category: IIB.b) in ready to use form is max. 250g/litre of VOC. The VOC content of this product in ready to use form is max. 250g/litre. Depending on the chosen mode of use, the actual ready to use VOC of this product may be lower than that specified by the EU Directive code.		

These products are for professional painting only, and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose. For Health and Safety information please refer to the Material Safety Data Sheet. March 2014.

AUTOLUX® & the AUTOLUX® logo are trademarks of PPG Industries Ohio, Inc. © 2014 PPG Industries. All rights reserved.

PPG Industries (UK) Ltd, Auto Refinish Customer Service & Sales Group, Needham Road, Stowmarket, Suffolk IP14 2AD, Tel: 01449 771775